

MATERIAL SAFETY DATA SHEET

Lubchem, Inc. 23609 W. Hardy Rd. Spring, TX 77373

Telephone (281) 350-9600

8/13/2008

NFPA	
Health:	0
Flammability:	1
Reactivity:	0

Section I - Product Identification

Product Name: Everlast 1000

Product Type: Valve Lubricant / Sealant

Section II - Hazardous Ingredients / Identity Information

Components	CAS Number	%	EXPOSURE LIMITS
Proprietary Mixture	N/A	100	N/A

Special Hazard Designations

DOT (49 CFR172): Not regulated

OSHA (29CFR1910.1200) Evaluation: Non hazardous

EPA/TSCA Listed Ingredients:None

Section III - Physical / Chemical Characteristics

Boiling Point: N/A

Specific Gravity (H₂O = 1): 1.12

Vapor Pressure (mm Hg.): N/A

Melting Point: None

Vapor Density (Air =1): N/A

Evaporation Rate (Butyl Acetate =1): N/A

Solubility in Water: Insoluble

Appearance / Odor: White / Slight odor

Section IV - Fire and Explosion Hazard Data

Flash Point (C.O.C.): 441 F

Flammable Limits- LEL: N/A UEL: N/A

Extinguishing Media: Foam, Carbon Dioxide, Dry Chemical, Sand

Special Fire Fighting Procedures: Standard fireman's protection and self contained breathing apparatus.

Unusual Fire and Explosion Hazards: Water may cause frothing.

Section V - Reactivity Data

Stability: Material is Stable

Incompatibility (materials to avoid): Strong oxidizing agents.

Hazardous Decomposition Products: Oxides of Carbon when burned.

Hazardous Polymerization: Will not occur

Section VI - Health Hazard Data

Health Hazards (Chronic): None Known

Carcinogenity: NTP: No IARC Monographs: No OSHA Regulated: No

Signs and Symptoms of Exposure:

Eyes: Mechanical irritant, prolonged exposure may cause irritation.

Inhalation: No effects known.

Ingestion: Moderately irritating by ingestion.

Skin: In contact with the skin product acts as slight local irritant and allergen.

Medical Conditions Generally Aggravated by Exposure: None known.

Emergency and First Aid Procedures:

Eyes: Flush eyes with water for 15 minutes while holding eyelids open. If irritation persists get medical attention.

Inhalation: First aid not anticipated to be needed

Ingestion: If ingested get medical attention.

Skin: Wash thoroughly with soap and water, launder soiled clothing before reuse.

MATERIAL SAFETY DATA SHEET

Lubchem, Inc. 23609 W. Hardy Rd. Spring, TX 77373
Telephone (281) 350-9600
8/13/2008

Section VII - Precautions for Safe Handling and Use

Steps To Be Taken In Case Material Is Released or Spilled: Attempt to recover. Pick up small spills with shovel or spatula.

Waste Disposal Method: Comply with all governmental regulations.

Precautions To Be Taken In Handling and Storage: Do not store containers in direct sunlight, keep containers away from excessive heat.

Other Precautions: N/D

Section VIII - Control Measures:

Respiratory Protection (Specify Type): None expected to be required

Ventilation - Local Exhaust: Acceptable

Protective Gloves: Neoprene Coated Gloves

Eye Protection: Safety Glasses

Work / Hygienic Practices: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area.

This document is prepared pursuant to the OSHA Hazard Communication Standard (29CFR1910.1200). The information herein is given in good faith, but no warranty, express or implied, is made. Consult Lubchem, Inc. For further information: 281-350-9600.

Abbreviations: N/A: Not Applicable N/D: Not Determined