

MATERIAL SAFETY DATA SHEET

Lubchem, Inc. 23609 W. Hardy Rd. Spring, TX 77373
Telephone (281) 350-9600
Revision 8/24/06

NFPA CODES

Health	1
Flammability	0
Reactivity	0
Special	COR

Section I - Product Identification

Product Name: Lubchem V-Clean
Product Type: Valve Cleaner
Formula/CAS No.: Complex Mixture

Section II - Hazardous Ingredients / Identity Information

Hazardous Ingredients	CAS Number	%	Exposure Limits
Sodium Hydroxide	CAS # 1310-73-2	8	2mg/m (ceiling)

Section III - Physical / Chemical Characteristics

Boiling Point: >210 F
Specific Gravity (H₂O = 1): 0.987
Vapor Pressure (mm Hg.): .006@20C
Melting Point: N/A
Vapor Density (Air =1): >1

Evaporation Rate (Butyl Acetate =1): >1
Solubility in Water: Complete
Appearance/Odor: Amber liquid,
characteristic odor
pH: 11 @ 1% Solution

Section IV - Fire and Explosion Hazard Data

Flash Point (PMCC) >212F

Extinguishing Media: N/A

Special Fire Fighting Procedures: Use suitable extinguishing media to control surrounding fire.

Unusual Fire and Explosion Hazards: N/A

Section V - Reactivity Data

Stability: Material is stable

Conditions to Avoid: N/D

Incompatibility (materials to avoid): Amphoteric metals (zinc, aluminum, copper and brass), bleaching agents, oxidizers, organic acids, organic nitrogen compounds,

Hazardous Decomposition Products: Fumes of metal oxides.

Hazardous Polymerization: Will not occur

Section VI - Health Hazard Data

Health Hazards (Chronic): N/D

Signs and Symptoms of Over Exposure

Eyes: Eye contact with product may cause severe irritation, burns, irreversible damage, and blindness.

Inhalation: Inhalation of mist may cause irritation, nausea, headache, and pain, decreased breathing capacity, tissue destruction.

Ingestion: may cause severe irritation, burns, tissue ulceration, and gastrointestinal damage. Skin: contact may cause burns, tissue destruction, skin damage, effects may be delayed.

Medical Conditions Generally Aggravated by Exposure: Over exposure may aggravate disorders of the blood circulatory system, lungs - respiratory system.

Emergency and First Aid Procedures:

Eyes: Flush eyes with water for 15 minutes while lifting upper and lower eyelids and consult physician immediately.

Inhalation: Remove to fresh air, if not breathing give artificial respiration, if breathing is difficult give oxygen. Contact physician immediately.

MATERIAL SAFETY DATA SHEET

Lubchem, Inc. 23609 W. Hardy Rd. Spring, TX 77373

Telephone (281) 350-9600

Revision 12/1/02

Ingestion: Do not induce vomiting. Rinse mouth with water. Dilute stomach contents by drinking large quantities of water. Do not induce vomiting, if vomiting occurs spontaneously keep head below hips to prevent breathing vomit into lungs. Call physician immediately.

Skin: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing. Call a physician.

Section VII – Environmental Protection:

Steps To Be Taken In Case Material Is Released or Spilled: Contain spill immediately. Prevent entering any waterway by diking. Absorb with inert absorbent material (sand, clay, dirt, absorbent). Large spills should be diked and picked up with vacuum pumps, shovels, buckets or other means and placed in suitable containers.

Waste Disposal Method: Comply with all governmental regulations.

Section VIII – Special Precautions:

Precautions To Be Taken In Handling and Storage: Do not store containers in direct sunlight, keep containers away from excessive heat.

Other Precautions: Avoid contact with skin and eyes. Use good housekeeping practices and clean up spills promptly. Eye wash and safety shower should be in close proximity.

Section IX - Control Measures:

Respiratory Protection: If exposure to mist may occur use a NIOSH respirator approved for your conditions of exposure.

Ventilation - Local Exhaust: Acceptable

Eye Protection: Chemical splash goggles with full-face shield recommended.

Protective Gloves: Rubber or neoprene.

Other Protective Clothing or Equipment: Chemical resistant clothing, rubber apron and rubber boots.

Work / Hygienic Practices: Safety shower and eye wash fountain.

Section X – Transportation Data

DOT Proper Shipping Name: Corrosive Liquid, n.o.s. (contains Sodium Hydroxide), 8, UN1760, PG III

Label Requirements: Corrosive

Section XI – Regulatory Information

All ingredients are listed on the TSCA inventory

The reportable quantity for sodium hydroxide is 1000 lbs. / 454 kgs

This document is prepared pursuant to the OSHA Hazard Communication Standard (29CFR1910.1200). The information herein is given in good faith, but no warranty, express or implied, is made. Consult Lubchem, Inc. For further information: 281-350-9600.

Abbreviations: N/A: Not Applicable N/D: Not Determined